



- Category**
- Rod Wiper, Snap Fit
- Construction**
- Orange Hyslip 55°D polymer with knifed wiping lip
- Housing**
- Open rectangular groove in one piece gland
- Duty**
- Heavy
- Features**
- Heel pressure release ribs
 - External lip for improved dirt exclusion
 - Crush lip for positive location
- Comments**
- Interchangeable with conventional D/B series rod wipers
- Manufacturer**
- Hallite
- Size Range**
- US Imperial

- Metric Specifications**
- Operating Conditions**
- | | |
|--------------------|---------------|
| Maximum Speed: | 4.0 m/sec |
| Temperature Range: | -40°C ~ 135°C |
- Surface Finish**
- | | |
|-----------------------|----------------|
| Dynamic Sealing Face: | 0.1 ~ 0.4 µmRa |
| Static Sealing Face: | 1.6 µmRa max |
| Other Faces: | 3.2 µmRa max |
- Imperial Specifications**
- Operating Conditions**
- | | |
|--------------------|---------------|
| Maximum Speed: | 12.0 ft/sec |
| Temperature Range: | -40°F ~ 275°F |
- Surface Finish**
- | | |
|-----------------------|----------------|
| Dynamic Sealing Face: | 4 ~ 16 µinCLA |
| Static Sealing Face: | 63 µinCLA max |
| Other Faces: | 125 µinCLA max |

Imperial Sizes

Part No.	Ød	ØD	H	ØT	t
Tolerances		±0.003	+0.004 -0	+0.010 -0	
D1000-520P	1.000	1.375	0.187	1.245	0.305
D1250-520P	1.250	1.625	0.187	1.495	0.305
D1375-520P	1.375	1.750	0.187	1.620	0.305
D1500-520P	1.500	1.875	0.187	1.745	0.305
D1750-520P	1.750	2.125	0.187	1.995	0.305
D2000-520P	2.000	2.500	0.249	2.327	0.395
D2250-520P	2.250	2.750	0.249	2.577	0.395

Imperial Sizes (cont'd)

Part No.	Ød	ØD	H	ØT	t
D2500-520P	2.500	3.000	0.249	2.827	0.395
D2750-520P	2.750	3.250	0.249	3.077	0.395
D3000-520P	3.000	3.500	0.249	3.327	0.395
D3500-520P	3.500	4.000	0.249	3.827	0.395
D3750-520P	3.750	4.250	0.249	4.077	0.395
D4000-520P	4.000	4.500	0.249	4.327	0.395
D4500-520P	4.500	5.250	0.374	4.993	0.585
D6000-520P	6.000	6.750	0.374	6.493	0.585