



- Category**
- Rod Wiper, Snap Fit
- Construction**
- Blue Hythane 181 with knifed wiping lip
- Housing**
- Open angled groove in one piece gland
- Duty**
- Light
- Features**
- Upgrade for K series grooves
  - Manufactured from industry leading polymer
  - Heel pressure release ribs
- Manufacturer**
- Hallite
- Size Range**
- Imperial

- Metric Specifications**
- Operating Conditions**
- |                    |               |
|--------------------|---------------|
| Maximum Speed:     | 4.0 m/sec     |
| Temperature Range: | -45°C ~ 110°C |
- Surface Finish**
- |                       |                |
|-----------------------|----------------|
| Dynamic Sealing Face: | 0.1 ~ 0.4 µmRa |
| Static Sealing Face:  | 1.6 µmRa max   |
| Other Faces:          | 3.2 µmRa max   |
- Imperial Specifications**
- Operating Conditions**
- |                    |               |
|--------------------|---------------|
| Maximum Speed:     | 12.0 ft/sec   |
| Temperature Range: | -50°F ~ 230°F |
- Surface Finish**
- |                       |                |
|-----------------------|----------------|
| Dynamic Sealing Face: | 4 ~ 16 µinCLA  |
| Static Sealing Face:  | 63 µinCLA max  |
| Other Faces:          | 125 µinCLA max |

### Imperial Sizes

Part No.	Ød	ØD	H	ØT	t
<i>Tolerances</i>		<i>+0.005 -0</i>	<i>+0.005 -0</i>	<i>+0.005 -0</i>	
UK1125-841	1.125	1.500	0.188	1.233	0.350
UK1250-841	1.250	1.625	0.188	1.358	0.350
UK1375-841	1.375	1.750	0.188	1.483	0.350
UK1500-841	1.500	1.875	0.188	1.608	0.350
UK1500A-841	1.500	1.750	0.176	1.608	0.275
UK1750-841	1.750	2.125	0.188	1.858	0.350
UK2000-841	2.000	2.375	0.188	2.108	0.350